

## N<sub>2</sub>O, 0-100% GAS ANALYSER | PIPED MEDICAL GAS VERIFICATION

The G210 is specifically designed for highly accurate measurement and verification of the quality of piped N<sub>2</sub>O and O<sub>2</sub> gases in hospitals.



### FEATURES

- 0 - 100% N<sub>2</sub>O
- 0 - 100% O<sub>2</sub>
- 0 - 500 ppm CO (optional)
- 0 w- 2000 ppm CO<sub>2</sub>
- Data storage with site and ID input
- User alarms

### BENEFITS

- 4 gases measured in one analyser
- Easy user calibration
- Quick verification of gas quality
- Enter specific site and IDs for monitoring points
- Identify contaminants CO and CO<sub>2</sub>

### SECTOR

Medical gas

### APPLICATIONS

- Hospital piped gases
- Leak detection



© Product designs and specifications are subject to change without notice. User is responsible for determining suitability of product.

## TECHNICAL SPECIFICATIONS

POWER SUPPLY		
Battery type	Li Ion	
Battery life	12 hours (10 hours with pump)	
Battery lifetime	600 cycles	
Battery charger	5v DC external power supply and internal charging circuit	
Charge time	4 hours	
Alternative power	5v DC power supply	
GAS RANGES		
Gases measured	N <sub>2</sub> O	By custom dual wavelength infra-red cell
	CO <sub>2</sub>	By custom dual wavelength infra-red cell
	O <sub>2</sub> (optional)	By internal electrochemical cell
	CO (optional)	By internal electrochemical cell
Oxygen cell lifetime	Approximately 3 years in air	
CO cell lifetime	Approximately 2 years in air	
Range	N <sub>2</sub> O	0-100%
	CO <sub>2</sub>	0-2000ppm
	O <sub>2</sub>	0-100%
	CO	0-500ppm
Measurement accuracy*	N <sub>2</sub> O	± 1% of range after calibration
	CO <sub>2</sub>	± 3% of range after calibration
	O <sub>2</sub>	± 0.5% of range after calibration
	CO	± 2ppm for 0-20ppm after calibration ± 5% of range from 21- 500ppm after calibration
Response time T <sup>90</sup>	CO <sub>2</sub>	≤ 20 seconds
	O <sub>2</sub>	≤ 60 seconds
	N <sub>2</sub> O	≤ 20 seconds
	CO	≤ 60 seconds
* plus accuracy of calibration gas used		
FACILITIES		
Visual and audible alarms	User selectable N <sub>2</sub> O, CO, CO <sub>2</sub> and O <sub>2</sub> alarm levels	
Communications	USB type B mini-connector, HID device class	
Data storage	1000 reading sets plus 270 events 50 site IDs and 300 sample point	

© Product designs and specifications are subject to change without notice. User is responsible for determining suitability of product.



## TECHNICAL SPECIFICATIONS CONTINUED

PUMP	
Flow	100cc / min typically
ENVIRONMENTAL CONDITIONS	
Operating temperature	0°C to +50°C
Relative humidity	5% to 95% non condensing
Barometric pressure	500 to 1500mb
IP rating	IP40
PHYSICAL	
Weight	500 grams
Size	L 165mm, W 100mm, D 55mm
Case material	ABS / polypropylene with silicone rubber inserts
Keys	17 resin capped silicone rubber keys
Display	Liquid crystal display, 128 x 64 pixel With RGB LED back-light
Gas sample filters	User replaceable PTFE water trap filter
Note: Due to Geotech's continuous programme of improvement, this specification is subject to change without prior notice.	
CERTIFICATION	
EN 50270 :2006	Electromagnetic compatibility- electrical apparatus for the detection and measurement of combustible gases, toxic gases or oxygen
EN61010-1:2010	Safety requirements for electrical equipment for measurement, control, and laboratory use. Part 1: General requirements

© Product designs and specifications are subject to change without notice. User is responsible for determining suitability of product.

© Product designs and specifications are subject to change without notice. User is responsible for determining suitability of product.

**QED Environmental Systems Ltd.**

Cyan Park- Unit 3, Jimmy Hill Way, Coventry, CV2 4QP, UNITED KINGDOM



qedenv.com



sales@qedenv.co.uk



+44 (0)333 800 0088

PAGE 4 OF 4 | D516-ISSUE.09